



COMPACT RFID REFRIGERATOR TS029

- » REAL-TIME INVENTORY VISIBILITY
- » PROACTIVE TEMPERATURE ALERTING
- » ELIMINATE MANUAL PROCESSES

SERVICE INFORMATION
DATE
DIN
SERIAL NUMBER
442
Model number and serial number
labels are on the inside of the door.
© 2011 TERSO



KNOW NOW.

Inventory Management Powered by RFID

BENEFITS OF THE TS029 - COMPACT REFRIGERATOR

- Maintain temperature range of 2°C to 8°C
- Prevent stock-outs; monitor expiry of products
- Customize product layout
- Protect critical inventory through secure access
- Provide regulatory compliance
- Tailor with your branding
- Integrate with external temperature monitoring systems



COMPONENT	SPECIFICATION
External Dimensions	42”H x 24”W x 26”D
Internal Dimensions	28”H x 21”W x 18”D
External Space Required	42”H x 24”W x 47”D Place 3” from back wall Allow 21” for door clearance
Volume	5.5ft ³
Weight	165lbs
Cooling Method	Forced air circulation
Access Control	LF badge
Optional Riser	23”H x 22”W x 24”D

COMMUNICATIONS	SPECIFICATION
RAIN RFID Frequency	902 to 928 MHz
Communications	Ethernet, optional cellular or wifi

POWER	SPECIFICATION
Electrical Power	120VAC, 60Hz, 2A
Power Consumption	160W max
Battery Backup	Up to 2hrs