

COMPACT INTERNATIONAL ECO-FRIENDLY RFID FREEZER TS047e

» REAL-TIME INVENTORY VISIBILITY

» PROACTIVE TEMPERATURE ALERTING

» ELIMINATE MANUAL PROCESSES



KNOW NOW.

Inventory Management Powered by RFID

BENEFITS OF THE TS047e - COMPACT FREEZER

- Reduce energy consumption by 50% over previous models
- Maintain temperature range of -25°C to -5°C
- Prevent stock-outs; monitor expiry of products
- Customize product layout
- Protect critical inventory through secure access
- Provide regulatory compliance
- Integrate with external temperature monitoring systems



COMPONENT	SPECIFICATION	
External Dimensions	1010 H x 595 W x 640 D (mm)	
Internal Dimensions	618 H x 492 W x 415 D (mm)	
External Space Required	1010 H x 595 W x 1270 D (mm) Place 76mm from back wall Allow 534mm for door clearance	
Volume	104L	
Weight	75kg	
Cooling Method	Forced air circulation	
Access Control	LF badge	
Optional Riser	584 H x 559 W x 610 D (mm)	

COMMUNICATIONS	SPECIFICATION	POWER	SPECIFICATION
RAIN RFID Frequency	864 to 868 MHz	Electrical Power	230VAC, 50Hz, 2A
L'ammunications	Ethernet, optional cellular or wifi	Power Consumption	106W max
		Battery Backup	Up to 2hrs

