



GRAM - + P □

COMPACT RFID REFRIGERATOR TS060

- » REAL-TIME INVENTORY VISIBILITY
- » PROACTIVE TEMPERATURE ALERTING
- » ELIMINATE MANUAL PROCESSES



KNOW NOW.

Inventory Management Powered by RFID

BENEFITS OF THE TS060 - COMPACT REFRIGERATOR

- Maintain temperature range of 2°C to 12°C
- Prevent stock-outs; monitor expiry of products
- Customize product layout
- Protect critical inventory through secure access
- Provide regulatory compliance
- Tailor with your branding
- Integrate with external temperature monitoring systems



COMPONENT	SPECIFICATION
External Dimensions	1010 H x 595 W x 620 D (mm)
Internal Dimensions	618 H x 492 W x 415 D (mm)
External Space Required	1010 H x 595 W x 1270 D (mm) Place 76mm from back wall Allow 534mm for door clearance
Volume	104L
Weight	75kg
Cooling Method	Forced air circulation
Access Control	LF badge
Optional Riser	584 H x 559 W x 610 D (mm)

COMMUNICATIONS	SPECIFICATION
RAIN RFID Frequency	864 to 868 MHz
Communications	Ethernet, optional cellular or wifi

POWER	SPECIFICATION
Electrical Power	230VAC, 50Hz, 2A
Power Consumption	84W max
Battery Backup	Up to 2hrs