



ULTRA LOW TEMPERATURE UNDER COUNTER RFID FREEZER TS079

- » SPACE-SAVING COMPACT DESIGN
- » PROACTIVE TEMPERTURE ALERTING
- » ELIMINATE MANUAL PROCESSES



KNOW NOW.

Inventory Management Powered by RFID

BENEFITS OF THE TS079 - UNDER COUNTER ULT

- Maintain temperature range of -86°C to -50°C
- Prevent stock-outs; monitor expiry of products
- Protect critical inventory through secure access
- Provide regulatory compliance
- Tailor with your branding
- Integrate with external temperature monitoring systems



COMPONENT	SPECIFICATION
External Dimensions	32.7"H x 35.4"W x 25"D
Internal Dimensions	25.2"H x 18.9"W x 13"D
External Space Required	32.7"H x 40"W x 50"D Place 3" from back wall Allow 21" for door clearance
Volume	3.6ft ³
Weight	265lbs
Cooling Method	2-stage cascade system
Access Control	LF badge

COMMUNICATIONS	SPECIFICATION
RAIN RFID Frequency	902 to 928 MHz
Communications	Ethernet, optional cellular or wifi

POWER	SPECIFICATION
Electrical Power	120VAC, 60Hz, 5A
Power Consumption	367W max
Battery Backup	Up to 2hrs