

# RFID SURFACE READ POINT TS082

- » INCREASE PRODUCT VISIBILITY
- » ELIMINATE MANUAL PROCESSES
- » ENSURE PRODUCT INTEGRITY

 **TERSO**  
SOLUTIONS, INC.

 **TERSO**  
SOLUTIONS, INC.

## BENEFITS OF THE TS082 - SURFACE READ POINT

- Optimize inventory levels and reduce shrinkage
- Prevent stock-outs; monitor expiry of products
- Receive item variance alerting and reporting
- Provide regulatory compliance
- Tailor with your branding
- Integrate with existing inventory platforms



COMPONENT	SPECIFICATION
External Dimensions	1.4"H x 25.8"W x 21.5"D
Weight	18lbs
Items Weight (max)	40lbs
Temperature Range	0°C to 50°C
Max Number of Tagged Items on Tray	100
Surface Material	ABS Plastic
Installation Cart Mounting	Cable ties to secure to a 24" rack
Desktop	Optional feet for setting on hard surfaces

COMMUNICATIONS	SPECIFICATION
RAIN RFID Frequency	902 to 928 MHz
Communications	Ethernet (LAN)
RFID Read Area	Adjustable from ~6" to 2'

POWER	SPECIFICATION
Electrical Power	PoE 802.3af
Power Consumption	10W max
RFID Power	0.25W
Accessories	Power over Ethernet Injector (optional); DC power supply (optional)