



RFID TAG READER TS089

- » READS UP TO 65 TAGS PER SECOND
- » RAIN RFID TECHNOLOGY
- » COMPACT AND EASY TO USE



KNOW NOW.

Inventory Management Powered by RFID

BENEFITS OF THE TS089 - RFID TAG READER

- Configurable for specific workflows, including quickly entering RFID tag EPCs into OnSight and other software
- Read distance: configurable up to 2 meters (6ft) dependent on power level and tag size
- Certified for use globally
- LEDs indicate successful tag read
- Audible confirmation



COMMUNICATIONS	SPECIFICATION
RFID Antenna	Internal, optimized for EU or NA frequency range
RF Read Range	Adjustable from 4" to 6'
Region Selections for US Band	FCC (NA, SA), Argentina, Australia, Bangladesh, China, Indonesia, Japan, Korea, Macao, Malaysia, New Zealand, Philippines, Singapore, Taiwan, Thailand
Region Selections for EU Band	ETSI (EU), Hong Kong, India, Russia, Vietnam

COMPONENT	SPECIFICATION
External Dimensions	61mm (W) x 133mm (L) x 20mm (H)
Temperature	Operating 0° to +50°C; storage -40°C to +70°C
Interfaces	USB HID keyboard emulation

POWER	SPECIFICATION
Power Consumption (Max)	USB Powered: 3.5 W
Power Consumption (Idle)	USB Powered: 1.0 W