

UNDERCOUNTER RFID REFRIGERATOR

Ensure peace of mind with the Undercounter RFID Refrigerator. Leave manual inventory management behind with proactive monitoring and 24/7 temperature tracking, plus real-time insight to your inventory. Its compact design and small footprint allow you to track high-value inventory without compromising space.



FEATURES

AT A GLANCE

Model number	US TS097
External dimension H x W x D	34.0 in. x 23.75 in. x 24.5 in.
Internal dimension H x W x D	23.5 in. x 17.5 in. x 17.0 in.
Volume	4.6 ft ³
Device weight	130.0 lbs
Access control	LF pass reader
Cooling method	Forced air cooled
Operating temperature range	+1.0 °C to +10.0 °C
RAIN RFID frequency	902 to 928 MHz
Communications	Ethernet, optional cellular
Electrical power & frequency	120 VAC, 60 Hz, 2 A
Power consumption	1.15 kWh/day
RFID battery backup	24 V SLA 1.3 Ah
Optional riser H x W x D	23.0 in. x 22.0 in. x 24.0 in.
Certifications	RAIN, SGS, FCC, SNAP, EnergyStar



BENEFITS

- Maintain temperature range of +1.0 °C to +10.0 °C
- Prevent stock-outs
- Monitor expiry of products
- Customize product layout
- Protect critical inventory through secure access
- Provide regulatory compliance
- Tailor with your branding
- Integrate with third-party inventory temperature monitoring systems

	APPLICATIONS	LOCATION USE
Undercounter RFID Refrigerator in action	Pharmaceuticals, medications, and vaccines Reagents Laboratory samples Refrigerated tissue & biologics Cardiovascular products Orthopedic products Refrigerated consignment inventory	Hospitals Stockrooms Research labs Pharmacies Aerospace Consignment inventory
WHAT IS IT GOOD FOR?		

*Specifications subject to change without notice