

COUNTERTOP RFID REFRIGERATOR

Ensure security and integrity of your inventory with the convenient access to the Countertop RFID Refrigerator. Easily install this device on any standard countertop and get started managing your critical inventory. With a temperature range of +1.0 °C to +10.0 °C, you'll know that products are kept cool and secure in this compact yet efficiently designed refrigerator.



FEATURES

AT A GLANCE

Model number	US TS098
External dimension H x W x D	23.0 in. x 17.25 in x 19.25 in.
Internal dimension H x W x D	15.75 in. x 14.0 in. x 9.0 in
Volume	1.0 ft ³
Device weight	64.0 lbs
Access control	LF pass reader
Operating temperature range	+1.0 °C to +10.0 °C
Cooling method	Forced air cooled
RAIN RFID frequency	902 to 928 MHz
Communications	Ethernet, optional cellular
Electrical power & frequency	120 VAC, 60 Hz, 2 A
Power consumption	1.2 kWh/day
RFID battery backup	24 V SLA 1.3 Ah
Certifications	RAIN, SNAP, SGS, EnergyStar



BENEFITS

- Maintain temperature range of +1.0 °C to +10.0 °C
- Prevent stock-outs
- Monitor expiry of products
- Protect critical inventory through secure access
- Provide regulatory compliance
- Tailor with your branding
- Integrate with external temperature tracking systems

Countertop RFID
Refrigerator in action

APPLICATIONS

**Reagent and laboratory
Biologics & biologic samples
Pharmaceuticals
Cardiovascular products
Orthopedic products**

LOCATION USE

**Hospitals
Research labs
Tissue storage facilities
Pharmacies
Stockrooms
Ambulatory surgery centers
Consignment inventory**

WHAT IS IT GOOD FOR?

*Specifications subject to change without notice