

MIDSIZE RFID REFRIGERATOR

Not too small, not too big, but just right. The Midsize RFID Refrigerator offers flexible storage space with a temperature range of +1.0 °C to +10.0 °C, all to ensure inventory security, visibility and ease-of-use.



FEATURES

AT A GLANCE

Model Number	US TS099
External dimension H x W x D	60.0 in. x 26.5 in. x 23.8 in.
Internal dimension H x W x D	53.0 in. x 20.0 in. x 18.0 in.
Volume	10.5 ft ³
Device weight	200.0 lbs
Access control	LF pass reader
Operating temperature range	+1.0 °C to +10.0 °C
Cooling method	Forced air cooled
RAIN RFID frequency	902 to 928 MHz
Communications	Ethernet, optional cellular
Electrical power & frequency	115 VAC, 60 Hz, 3 A
Power consumption	2.5 kWh/day
RFID battery backup	12 VDC SLA, qty 2
Certifications	RAIN, SNAP, SGS, FCC, EnergyStar



BENEFITS

Maintain temperature range of +1.0 °C to +10.0 °C

Prevent stock-outs

Monitor expiry of products

Customize product layout

Protect critical inventory through secure access

Provide regulatory compliance

Tailor with your branding

Integrate with third-party temperature monitoring systems

Midsize RFID Refrigerator
in action

WHAT IS IT GOOD FOR?

APPLICATIONS

Reagent and laboratory
media storage
Biologics & biologic samples
Pharmaceuticals
Cardiovascular products
Adhesives
Refrigerated consignment
inventory

LOCATION USE

Hospitals
Research labs
Tissue storage facilities
Pharmacies
Biobanks
Crime labs
Stockrooms
Aerospace
Consignment inventory

*Specifications subject to change without notice