

COUNTERTOP RFID CABINET

The Countertop RFID Cabinet's small but powerful design allows you to track inventory in real-time and customize your product layout all with convenience in mind. It's the perfect solution for a variety of spaces and applications.



FEATURES

AT A GLANCE

Model number	US EUR TS083
External dimension H x W x D	US 15.0 in. x 14.0 in. x 19.0 in. EUR 381 mm. x 356 mm. x 483 mm.
Internal dimension H x W x D	US 13.0 in. x 12.0 in. x 17.0 in. EUR 330 mm. x 305 mm. x 432 mm.
Volume	US 1.5 ft ³ EUR 44 L
Device weight	US 40 lbs EUR 18 kg
Access control	Keyed access
Storage configuration	Up to 4 drawers
RAIN RFID frequency	US 902 to 928 MHz EUR 865 to 868 MHz
Communications	Ethernet, optional cellular
Electrical power & frequency	US 120 VAC, 60 Hz, 1 A EUR 230 VAC, 50 Hz, 1 A
Power over Ethernet	IEEE 802.3 af
Power consumption	10 W max
Certifications	RAIN, SGS, UL, cUL, FCC, RoHS, CE



BENEFITS

- Optimize inventory levels
- Prevent stock-outs
- Monitor expiry of products
- Customize your product layout
- Provide regulatory compliance
- Protect critical inventory through keyed access
- Tailor with your branding
- Integrate with existing inventory platforms

Countertop RFID
Cabinet in action

WHAT IS IT GOOD FOR?

APPLICATIONS	LOCATION USE
Dental implants Biologics Reagents Orthopedic implants Pharmaceuticals & controlled substances Cardiovascular products Orthopedic supplies Consignment inventory	Dental offices Hospitals Research labs Pharmacies Stockroom Government agencies Aerospace Consignment inventory

*Specifications subject to change without notice