

MIDSIZE RFID FREEZER

Terso Solutions' Midsize RFID Freezer offers all of the same benefits as the Undercounter RFID Freezer, but with a larger interior volume. With an operational temperature range of $-25.0\text{ }^{\circ}\text{C}$ to $-15.0\text{ }^{\circ}\text{C}$, the freezer ensures temperature critical inventory is properly maintained.



FEATURES

AT A GLANCE

Model number	US EUR TS093
External dimension H x W x D	75.0 in. x 24.0 in. x 24.0 in.
Internal dimension H x W x D	63.0 in. x 19.0 in. x 17.0 in.
External Space Required H x W x D	63.0 in. x 27.0 in. x 52.0 in. Allow for 4 in. of clearance on the sides and rear of the device, and 24 in. on the front for door clearance
Volume	10.4 ft ³
Device weight	214.0 lbs
Access control	LF pass reader
Operating temperature range	-25.0 °C to -15.0 °C
Cooling method	In-shelf tubing
RAIN RFID frequency	902 to 928 MHz
Communications	Ethernet, optional cellular
Electrical power & frequency	115 VAC, 60 Hz, 3.5 A
Power consumption	2.0 kWh/day
RFID battery backup	12 VDC SLA (2 count)
Certifications	RAIN, SGS, FCC, RoHS, EnergyStar, SNAP



BENEFITS

- Maintain temperature range of -25.0 °C to -15.0 °C
- Prevent stock-outs
- Monitor expiry of products
- Customize product layout
- Protect critical inventory through secure access
- Provide regulatory compliance
- Tailor with your branding
- Integrate with third-party temperature monitoring systems

Midsized RFID
Freezer in action

WHAT IS IT GOOD FOR?

APPLICATIONS

- Reagent and laboratory media storage
- Biologics & biologic samples
- Pharmaceuticals
- Cardiovascular products
- Orthopedic products
- Adhesives
- Frozen consignment

LOCATION USE

- Hospitals
- Research labs
- Tissue storage facilities
- Pharmacies
- Biobanks
- Crime labs
- Stockrooms
- Aerospace
- Consignment inventory

*Specifications subject to change without notice